




Shield in Deployed Position



Shield in Stowed Position

Product Details

Model Number	AMP1-12HTS-MW
ATPV	12 cal/cm ²
Bracket Type	Weight Compensating Slotted Cap Bracket
Material	Shield- Polycarbonate Bracket- Nylon
Color	Shield- Grey Bracket- Blue
Shield Coatings	Non-permanent Antifog
Product Weight	0.70 lbs.
Specification	NFPA 70E ASTM F2178 ANSI Z87+S
Description	Arc flash protection face shield kit with nanoparticle lens, transparent ergonomic chin protector & weight compensating cap bracket for Milwaukee® safety helmets
Competitive Advantage	<ul style="list-style-type: none"> • Grey tint for enhanced color recognition • Weight compensating bracket centers the shield in the stowed position, providing a compact assembly and improving comfort • Nanoparticle formulation for a more robust & longer-lasting shield • Standard shield coating features a nonpermanent anti-fog • Transparent ergonomic chin protector for excellent downward vision • LeverLock® attachment system for easy shield replacement • Press-to-release slotted adapters for easy bracket removal • Compatible w/ Paulson ALM™ flashlight system
Applications	Used for dielectric head & face protection against the hazards of arc flash. Not for welding.
Safety Helmet Compatibility	Milwaukee®
Country of Origin	USA
CA Prop. 65 Warning	 Cancer & Reproductive - For more information, go to www.P65Warnings.ca.gov
Note	<ul style="list-style-type: none"> • Safety helmet not included • Flashlight system sold separately

