Field Mount Tactical Face Shield Model DK5-X.250AFS





P	roduct Details
Model Number	DK5-X.250AFS
Material	Shield: Polycarbonate
	Attachment System: Plastic Alloy, Steel
	Inserts & nylon fabric strap
Color	Shield: Clear
	Attachment System: Black
Shield Coatings	Antifog / Anti-Abrasion
Shield Length	6″
Shield Thickness	0.250"
Product Weight	1.22 lbs.
Specification	NIJ 0104.02
Helmet	PASGT
Compatibility	Tactical face shield designed to fit most
Description	PASGT ballistic combat helmets with front
	brim
Competitive	 Shield thickness of 0.250" has a V-50
Advantage	rating for fragmentation
	 Shield length of 6" allows for gas mask
	clearance
	Shield locks into the stowed or
	deployed positions and can be
	released with one hand.
	 Premium antifog & anti-abrasion
	coatings
	Optically correct lens minimizes
	distortion & optimizes visibility
	 Integral rubber seal provides
	protection from liquids.
	 Pivot and lock assembly can be
	transferred to right or left of the shield
	for individual preference.
	Field mount attachment system
	requires no tools
Applications	Police, Sheriff, National Guard, University
Country of Outside	Police, Riot Squad, Jail, Military, SWAT
Country of Origin CA Prop. 65	USA Cancor & Poproductivo – For moro
Warning A	Cancer & Reproductive - For more information, go to
	www.P65Warnings.ca.gov
Export Control	This item is controlled by the U.S.
Statement	Government and authorized for export
	only to the country of ultimate destination
	for use by the ultimate consignee or end-
	user(s) herein identified. It may not be
	resold, transferred, or otherwise disposed
	of, to any other country or to any person
	other than the authorized ultimate
	consignee or end-user(s), either in their
	original form or after being incorporated
	into other items, without first obtaining
	approval from the U.S. Government or as
	otherwise authorized by U.S. law and
	regulations.
Note	Helmet not included



Paulson Manufacturing Corp. 46752 Rainbow Canyon Road, Temecula, CA 92592 Phone: 951-676-2451 | Toll Free: 800-542-2451 | Fax: 951-676-3481 info@paulsonmfg.com | www.paulsonmfg.com

