



Shield in deployed position



Shield in stowed position



Product Details	
Model Number	DK7-X.250AF-RULE
Material	Shield: Polycarbonate Attachment System: Plastic Alloy, Aluminum, Steel Inserts/Components Liquid Seal: Rubber
Color	Shield: Clear Attachment System: Black
Shield Coatings	Antifog / Anti-Abrasion
Shield Length	6"
Shield Thickness	0.250"
Product Weight	1.48 lbs.
Specification	NIJ 0104.02
Rail Compatibility	United Shield®
Description	Rail-mount tactical face shield designed to fit United Shield® ballistic combat helmets with side rail systems.
Competitive Advantage	Shield thickness of 0.250" has a V-50 rating for fragmentation Shield length of 6" allows for gas mask clearance Three shield lock positions Aluminum arms extend shield to provide excellent ventilation & clearance Extended rubber barrier prevents liquid pass-through and fits over NVG mount Premium antifog & anti-abrasion coatings Optically correct lens minimizes distortion & optimizes visibility Rail mount attachment system requires no tools
Applications	Police, Sheriff, National Guard, University Police, Riot Squad, Jail, Military, SWAT
Country of Origin	USA
CA Prop. 65 Warning	Cancer & Reproductive - For more information, go to www.P65Warnings.ca.gov
Export Control Statement	This item is controlled by the U.S. Government and authorized for export only to the country of ultimate destination for use by the ultimate consignee or enduser(s) herein identified. It may not be resold, transferred, or otherwise disposed of, to any other country or to any person other than the authorized ultimate consignee or end-user(s), either in their original form or after being incorporated into other items, without first obtaining approval from the U.S. Government or as otherwise authorized by U.S. law and regulations.
Note	Helmet not included

